

RESPONSE UNDER 37 C.F.R. 1.111 U.S. Application 09/305,019

PATENT Docket No. 10151-1

AMENDMENTS TO THE CLAIMS:

1-3 (Cancelled)

- 4. (Previously Amended) A process for producing a monoalkylated aromatic compound comprising the steps of:
 - (a) contacting an alkylatable aromatic compound with an alkylating agent in the presence of an alkylation catalyst in an alkylation reaction to provide a product comprising said monoalkylated aromatic compound and a polyalkylated aromatic compound, and then
 - (b) contacting the polyalkylated aromatic compound from step
 (a) with said alkylatable aromatic compound in the liquid phase and in the
 presence of a transalkylation catalyst in a transalkylation reactor separate
 from said alkylation reactor, said transalkylation catalyst comprising TEAmordenite having an average crystal size of less than 0.5 micron to produce
 said monoalkylated aromatic compound.
- 5. (Original) The process of claim 4, wherein the alkylation step (a) is conducted in the liquid phase.
- 6. (Original) The process of claim 4, wherein the alkylating agent includes an alkylating aliphatic group having 1 to 5 carbon atoms.
- 7. (Original) The process of claim 4, wherein the alkylating agent is ethylene or propylene and the alkylatable aromatic compound is benzene.
- 8. (Original) The process of claim 4, wherein the alkylation catalyst of step (a) is selected from MCM-22, MCM-49, MCM-56 and zeolite beta.





RESPONSE UNDER 37 C.F.R. 1.111 U.S. Application 09/305,019

PATENT Docket No. 10151-1

- 9. (Original) The process of claim 4, wherein step (a) is conducted at a temperature between about 300° and 600°F (about 150° and 316°C), a pressure up to about 3000 psig (20875 kPa), a space velocity between about 0.1 and 20 WHSV, based on the ethylene feed, and a ratio of the benzene to the ethylene between about 1:1 and 30:1 molar.
- 10. (Currently Amended) The process of claim 4, wherein step (b) is conducted at a temperature of 100 to 260°C, a pressure of 10 to 50 barg, a weight hourly space velocity of 1 to 10 on total feed, and benzene/polyalkylated benzene weight ration 1:1 to 6:1.
- 11. (New) The process of claim 4, wherein the TEA-mordenite was produced by crystallization from a synthesis mixture comprising a Si/Al₂ molar ratio of less than 90.
- 12. (New) The process of claim 4, wherein the TEA-mordenite was produced by crystallization from a synthesis mixture comprising a Si/Al₂ molar ratio of between about 35 and about 50.

